



SAFETY DATA SHEET

PRO - ALCOHOL ENHANCED FLUX REMOVER-PROCLEAN, BULK

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	PRO - ALCOHOL ENHANCED FLUX REMOVER-PROCLEAN, BULK
Product number	MCC-PROG, MCC-PROGG, MCC-PROL, MCC-PROLi, MCC-PROLG, MCC-PROP, MCC-PROPi, MCC-PROD, MCC-PROJG, MCC-PROGI
Synonyms; trade names	PRO - PROCLEAN SOLVENT, BULK

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Cleaning agent.
------------------------	-----------------

1.3. Details of the supplier of the safety data sheet

Supplier	MICROCARE EUROPE BVBA VEKESTRAAT 29 B11 INDUSTRIEZONE 'T SAS 1910 KAMPENHOUT, Belgium Phone +32.2.251.95.05 Fax +32.2.400.96.39
Manufacturer	MICROCARE CORPORATION 595 John Downey Drive New Britain, CT 06051 United States of America CAGE: OATV9 Tel: +1 800-638-0125, +1 860-827-0626 Fax: +1 860-827-8105 techsupport@microcare.com

1.4. Emergency telephone number

Emergency telephone	CHEMTREC UK (London) +(44)-870-8200418 +1 703-741-5970 (from anywhere in the world)
----------------------------	---

SECTION 2: Hazards identification


2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Flam. Liq. 2 - H225
Health hazards	Eye Irrit. 2 - H319 STOT SE 3 - H336
Environmental hazards	Not Classified

Physicochemical	The product is highly flammable. Vapours may form explosive mixtures with air. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers.
------------------------	--

2.2. Label elements

PRO - ALCOHOL ENHANCED FLUX REMOVER-PROCLEAN, BULK**Pictogram****Signal word**

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P243 Take action to prevent static discharges.
 P261 Avoid breathing vapour/ spray.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

Supplemental label information

EUH210 Safety data sheet available on request.
 RCH001a For use in industrial installations only.

Contains

PROPAN-2-OL

Supplementary precautionary statements

P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical equipment.
 P242 Use non-sparking tools.
 P264 Wash contaminated skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTRE/doctor if you feel unwell.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

ETHANOL		30-60%
CAS number: 64-17-5	EC number: 200-578-6	REACH registration number: 05-2114285309-40-0000
Classification		
Flam. Liq. 2 - H225		

PRO - ALCOHOL ENHANCED FLUX REMOVER-PROCLEAN, BULK

PROPAN-2-OL		30-60%
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 05-2114285306-46-0000
Classification		
Flam. Liq. 2 - H225		
Eye Irrit. 2 - H319		
STOT SE 3 - H336		

The full text for all hazard statements is displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

Composition

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	The product is flammable. CAUTION! First aid personnel must be aware of own risk during rescue! Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Due to the physical nature of this material it is unlikely that swallowing will occur. Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Never give anything by mouth to an unconscious person. Consult a physician for specific advice.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Vapours may cause drowsiness and dizziness. Headache. Irritation of nose, throat and airway.
Ingestion	Due to the physical nature of this material it is unlikely that swallowing will occur. Ingestion of large amounts may cause unconsciousness. May cause nausea, headache, dizziness and intoxication.
Skin contact	Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. May cause skin irritation/eczema.
Eye contact	May cause temporary eye irritation. Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

PRO - ALCOHOL ENHANCED FLUX REMOVER-PROCLEAN, BULK

Suitable extinguishing media Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is flammable. Heating may generate flammable vapours.

Hazardous combustion products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon.

5.3. Advice for firefighters

Protective actions during firefighting Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Avoid release to the environment. Do not discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Warn everybody of potential hazards and evacuate if necessary. If leakage cannot be stopped, evacuate area. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Do not eat, drink or smoke when using the product. Eliminate all sources of ignition. Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Earth container and transfer equipment to eliminate sparks from static electricity. Keep container tightly closed. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

PRO - ALCOHOL ENHANCED FLUX REMOVER-PROCLEAN, BULK

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Reference to other sections. Store away from incompatible materials (see Section 10).

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

ETHANOL

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

WEL = Workplace Exposure Limit

Additional Occupational Exposure Limits

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Avoid heat, flames and other sources of ignition.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body protection

Wear apron or protective clothing in case of contact.

Hygiene measures

Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Clear liquid.

Colour Colourless.

Odour Alcoholic.

PRO - ALCOHOL ENHANCED FLUX REMOVER-PROCLEAN, BULK

Odour threshold	Not determined. Not determined.
pH	No information available.
Melting point	No information available.
Initial boiling point and range	77°C/170.6°F @ 101.3 kPa
Flash point	12°C/54°F Tag closed cup.
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 2.0 %(V) Upper flammable/explosive limit: 12.7 %(V)
Other flammability	No information available.
Vapour pressure	5.2 kPa @ 20°C
Vapour density	1.82
Relative density	0.79
Bulk density	Not applicable.
Solubility(ies)	Soluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	The product is highly flammable. Vapours may form explosive mixtures with air.
Oxidising properties	There are no chemical groups present in the product that are associated with oxidising properties.

9.2. Other information

Refractive index	No information available.
Particle size	No information available.
Molecular weight	No information available.
Volatility	100%
Saturation concentration	No information available.
Critical temperature	No information available.
Volatile organic compound	No information available.
UDF Phrase 1	The product is flammable.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

PRO - ALCOHOL ENHANCED FLUX REMOVER-PROCLEAN, BULK

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Strong oxidising agents. Strong alkalis. Strong mineral acids.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Other health effects There is no evidence that the product can cause cancer.

Inhalation May cause respiratory system irritation. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion Not considered to be a significant hazard due to the small quantities used.

Skin contact Product has a defatting effect on skin. May cause skin irritation/eczema.

Eye contact Irritating to eyes. Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Acute and chronic health hazards Keep out of the reach of children.

Toxicological information on ingredients.

ETHANOL

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 20,000.0

ATE inhalation (vapours mg/l) 20,000.0

Carcinogenicity

IARC carcinogenicity IARC Group 1 Carcinogenic to humans.

PROPAN-2-OL

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Not listed.

SECTION 12: Ecological Information

PRO - ALCOHOL ENHANCED FLUX REMOVER-PROCLEAN, BULK

Ecotoxicity The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

12.1. Toxicity

Toxicity Not considered toxic to fish.

Ecological information on ingredients.

ETHANOL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: >10,000 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 7,800 mg/l, Daphnia magna

Acute toxicity - aquatic plants , 96 hours: 1000 mg/l, Freshwater algae

PROPAN-2-OL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 9,640 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 5102 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: >2,000 mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability The product is readily biodegradable.

Ecological information on ingredients.

ETHANOL

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

Ecological information on ingredients.

ETHANOL

Bioaccumulative potential Bioaccumulation is unlikely.

Partition coefficient No information available.

PROPAN-2-OL

Partition coefficient : 0.05

12.4. Mobility in soil

Mobility The product is soluble in water.

PRO - ALCOHOL ENHANCED FLUX REMOVER-PROCLEAN, BULK

Ecological information on ingredients.

ETHANOL

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Materials such as cleaning rags and paper wipes that are contaminated with flammable liquids may self-ignite after use and should be stored in designated fireproof containers with tight-fitting, self-closing lids. Reuse or recycle products wherever possible.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General Requirements for marking and labeling of package varies depending on mode of transport. If uncertain of proper markings and labeling, call MicroCare for assistance.

14.1. UN number

UN No. (ADR/RID)	1993
UN No. (IMDG)	1993
UN No. (ICAO)	1993
UN No. (ADN)	1993

14.2. UN proper shipping name

Proper shipping name (ADR/RID) UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL SOLUTION), 3, PGII

Proper shipping name (IMDG) UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL SOLUTION), 3, PGII

Proper shipping name (ICAO) UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL SOLUTION), 3, PGII

Proper shipping name (ADN) UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL SOLUTION), 3, PGII

14.3. Transport hazard class(es)

ADR/RID class	3
IMDG class	3
ICAO class/division	3

Transport labels



PRO - ALCOHOL ENHANCED FLUX REMOVER-PROCLEAN, BULK

14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ADN packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Not applicable.

EmS	F-E, S-D
Emergency Action Code	1Z
Hazard Identification Number (ADR/RID)	40
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	21/03/2018
Revision	35
Supersedes date	10/03/2017
SDS number	BULK - PRO
SDS status	Approved.
Hazard statements in full	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

PRO - ALCOHOL ENHANCED FLUX REMOVER-PROCLEAN, BULK

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.