



SAFETY DATA SHEET

SPR - HEAVY DUTY FLUX REMOVER - SUPRCLEAN, AEROSOL

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name SPR - HEAVY DUTY FLUX REMOVER - SUPRCLEAN, AEROSOL

Product number MCC-SPR, MCC-SPR101, MCC-SPR12Y, MCC-SPR19A

Synonyms; trade names "SPR - SUPRCLEAN Nonflammable Flux Remover", MCC-CBCSK

Recommended use of the chemical and restrictions on use

Application Cleaning agent.

Details of the supplier of the safety data sheet

Supplier MICROCARE CORPORATION

Manufacturer MICROCARE CORPORATION
595 John Downey Drive
New Britain, CT 06051
United States of America
CAGE: OATV9
Tel: + 1 800 638 0125, +1 860-827-0626
Fax: +1 860-827-8105
techsupport@microcare.com

Emergency telephone number

Emergency telephone CHEMTREC 1-800-424-9300 (within the U.S.)
+1 703-741-5970 (from anywhere in the world)

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Not Classified

Human health Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. Mild dermatitis, allergic skin rash.

Environmental The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Physicochemical Vapors are heavier than air and may travel along the floor and accumulate in the bottom of containers. Not considered to be a significant hazard due to the small quantities used. Gas or vapor displaces oxygen available for breathing (asphyxiant).

Label elements

Hazard statements NC Not Classified

SPR - HEAVY DUTY FLUX REMOVER - SUPRCLEAN, AEROSOL

Precautionary statements P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.
 P251 Pressurized container: Do not pierce or burn, even after use
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/ container in accordance with local regulations.

Supplemental label information Safety data sheet available on request. For use in industrial installations only.

3. Composition/information on ingredients

Mixtures

trans-DICHLOROETHYLENE	30-60%
CAS number: 156-60-5	

Classification

Flam. Liq. 2 - H225
 Acute Tox. 4 - H332
 Not relevant.

1,1,1,2,2,3,4,5,5,5-decafluoropentane	10-30%
CAS number: 138495-42-8	

Classification

Not relevant.

HFC-134a Tetrafluoroethane	10-30%
CAS number: 811-97-2	

Classification

Press. Gas, Liquefied - H280

ETHANOL	1-5%
CAS number: 64-17-5	

Classification

Flam. Liq. 2 - H225

The full text for all hazard statements is displayed in Section 16.

Composition comments The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of CFR 1900.1200 TSCA: The ingredients of this product are on the TSCA Inventory.

Composition

4. First-aid measures

Description of first aid measures

General information Never give anything by mouth to an unconscious person. Do not induce vomiting. Place unconscious person on the side in the recovery position and ensure breathing can take place. If breathing stops, provide artificial respiration.

SPR - HEAVY DUTY FLUX REMOVER - SUPRCLEAN, AEROSOL

Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Consult a physician for specific advice.
Skin Contact	Remove contaminated clothing and rinse skin thoroughly with water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Consult a physician for specific advice.

Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Vapors may cause headache, fatigue, dizziness and nausea. Difficulty in breathing. Upper respiratory irritation. Severe irritation of nose and throat.
Ingestion	May cause stomach pain or vomiting. Drowsiness, dizziness, disorientation, vertigo.
Skin contact	Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.
Eye contact	Irritation of eyes and mucous membranes. Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---------------------------------------------------------------------------

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	-----------------------------------------------------------------------------------------------

Special hazards arising from the substance or mixture

Flammability Class	The product is not flammable.
Specific hazards	Keep away from heat, sparks and open flame. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapors. Aerosol containers can explode when heated, due to excessive pressure build-up.
Hazardous combustion products	Heating may generate the following products: Toxic and corrosive gases or vapors. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. Oxides of carbon. Oxides of nitrogen.

Advice for firefighters

Protective actions during firefighting	Move containers from fire area if it can be done without risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Bursting aerosol containers may be propelled from a fire at high speed.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level.
-----------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SPR - HEAVY DUTY FLUX REMOVER - SUPRCLEAN, AEROSOL

Environmental precautions

Environmental precautions Contain spillage with sand, earth or other suitable non-combustible material. Avoid release to the environment.

Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation.

Reference to other sections See Section 11 for additional information on health hazards.

7. Handling and storage

Precautions for safe handling

Usage precautions Provide adequate ventilation. Avoid inhalation of vapors/spray and contact with skin and eyes. Keep away from heat, sparks and open flame. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapors.

Conditions for safe storage, including any incompatibilities

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

Reference to other sections. Store away from incompatible materials (see Section 10).

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

trans-DICHLOROETHYLENE

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 793 mg/m³

1,1,1,2,2,3,4,5,5,5-decafluoropentane

No information available that would effect occupational exposure limit values.

HFC-134a Tetrafluoroethane

Long-term exposure limit (8-hour TWA): OES 4240 mg/m³

ETHANOL

Short-term exposure limit (15-minute): ACGIH 1000 ppm 1880 mg/m³

A3

Long-term exposure limit (8-hour TWA): OSHA 1000 ppm 1900 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

OSHA = Occupational Safety and Health Administration.

Additional Occupational Exposure Limits

Ingredient comments ACGIH = US Standard. WEL = Workplace Exposure Limits

ETHANOL (CAS: 64-17-5)

Ingredient comments WEL = Workplace Exposure Limits

Exposure controls

SPR - HEAVY DUTY FLUX REMOVER - SUPRCLEAN, AEROSOL

Protective equipment



Appropriate engineering controls

No specific ventilation requirements. This product must not be handled in a confined space without adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination. Wear apron or protective clothing in case of contact.

Hygiene measures

No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products. When using do not eat, drink or smoke.

Respiratory protection

Vapors are heavier than air and may travel along the floor and accumulate in the bottom of containers. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Wear self-contained breathing apparatus with full facepiece.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Clear liquid. Aerosol.
Color	Colorless.
Odor	Slight. Ether.
Odor threshold	No information available.
pH	No information available.
Melting point	No information available.
Initial boiling point and range	41°C/106°F @ 101.3 kPa
Flash point	The product is not flammable.
Evaporation rate	No information available.
Evaporation factor	No information available.
Upper/lower flammability or explosive limits	Upper flammable/explosive limit: 14.4 %(V) Lower flammable/explosive limit: 5.0 %(V)
Other flammability	The product is not flammable. Aerosol ignition distance: none at 0.0 cm
Vapor pressure	37.9 kPa @ 25°C
Vapor density	3.4
Relative density	1.27
Bulk density	No information available.
Solubility(ies)	.4 g/l water @ 25°C
Partition coefficient	No information available.

SPR - HEAVY DUTY FLUX REMOVER - SUPRCLEAN, AEROSOL

Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.
Oxidizing properties	Not known.
Comments	Aerosol.
Refractive index	No information available.
Particle size	No information available.
Molecular weight	Not applicable.
Volatility	100%
Saturation concentration	No information available.
Critical temperature	No information available.
Volatile organic compound	This product contains a maximum VOC content of 1080 g/l.
Flammability	The product is not flammable.

10. Stability and reactivity

Reactivity	The following materials may react with the product: Strong alkalis.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	Will not polymerize.
Conditions to avoid	Keep away from heat, sparks and open flame. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapors.
Materials to avoid	Alkali metals. Alkaline earth metals. Powdered metal.
Hazardous decomposition products	Heating may generate the following products: Toxic and corrosive gases or vapors. Halogenated hydrocarbons. Hydrogen fluoride (HF). Carbon dioxide (CO ₂). Carbon monoxide (CO).

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 2,245.45

Inhalation	Vapors may irritate throat/respiratory system. A single exposure may cause the following adverse effects: Coughing. Difficulty in breathing.
Ingestion	May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication.
Skin Contact	Product has a defatting effect on skin. May cause allergic contact eczema.
Eye contact	May cause temporary eye irritation.

SPR - HEAVY DUTY FLUX REMOVER - SUPRCLEAN, AEROSOL

Medical Symptoms Gas or vapor in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.

Toxicological information on ingredients.

trans-DICHLOROETHYLENE

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE dermal (mg/kg) 5,000.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 114.0

Species Rat

ATE inhalation (vapours mg/l) 114.0

Skin corrosion/irritation

Animal data Not irritating. Rabbit

Human skin model test Data lacking.

Extreme pH Not applicable. Not corrosive to skin.

Serious eye damage/irritation

Serious eye damage/irritation Not irritating. Rabbit

Respiratory sensitization

Respiratory sensitization Data lacking.

Skin sensitization

Skin sensitization Not sensitizing. - Guinea pig: Not sensitizing.

Germ cell mutagenicity

Genotoxicity - in vitro This substance has no evidence of mutagenic properties.

SPR - HEAVY DUTY FLUX REMOVER - SUPRCLEAN, AEROSOL

Genotoxicity - in vivo	This substance has no evidence of mutagenic properties.
<u>Carcinogenicity</u>	
Carcinogenicity	Does not contain any substances known to be carcinogenic.
IARC carcinogenicity	Not listed.
NTP carcinogenicity	Not listed.
OSHA Carcinogenicity	Not listed.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No evidence of reproductive toxicity in animal studies.
Skin Contact	Skin irritation should not occur when used as recommended. May cause defatting of the skin but is not an irritant.
Eye contact	May cause eye irritation.
Acute and chronic health hazards	There is no evidence that the product can cause cancer.

HFC-134a Tetrafluoroethane

Other health effects	There is no evidence that the product can cause cancer.
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ gases ppmV)	567,000.0
Species	Rat
ATE inhalation (gases ppm)	567,000.0
Inhalation	Vapors irritate the respiratory system. May cause coughing and difficulties in breathing.
Ingestion	May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication.
Skin Contact	May cause allergic contact eczema. Contact with liquid form may cause frostbite.
Eye contact	May cause temporary eye irritation.

ETHANOL

<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	20,000.0
ATE inhalation (vapours mg/l)	20,000.0
<u>Carcinogenicity</u>	
IARC carcinogenicity	IARC Group 1 Carcinogenic to humans.

SPR - HEAVY DUTY FLUX REMOVER - SUPRCLEAN, AEROSOL

12. Ecological Information

Ecological information on ingredients.

trans-DICHLOROETHYLENE

Ecotoxicity Low acute toxicity to aquatic organisms.

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Ecotoxicity It is unlikely that the substance will dissolve in water in amounts big enough to have a toxic effect on fish and daphnies.

Toxicity Very toxic to aquatic organisms.

Ecological information on ingredients.

trans-DICHLOROETHYLENE

Acute toxicity - fish LC₅₀, 96 hours: 1350 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 220 mg/l, Daphnia magna

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Acute toxicity - fish LC₅₀, 96 hours: 13.9 mg/l, Onchorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates LC₅₀, 48 hours: 11.7 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: >120 mg/l, Algae

HFC-134a Tetrafluoroethane

Acute toxicity - fish LC₅₀, 96 hours: 450 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 980 mg/l, Daphnia magna

ETHANOL

Acute toxicity - fish LC₅₀, 96 hours: >10,000 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 7,800 mg/l, Daphnia magna

Acute toxicity - aquatic plants , 96 hours: 1000 mg/l, Freshwater algae

Persistence and degradability

Ecological information on ingredients.

ETHANOL

Persistence and degradability The product is expected to be biodegradable.

Bioaccumulative potential

SPR - HEAVY DUTY FLUX REMOVER - SUPRCLEAN, AEROSOL

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient No information available.

Ecological information on ingredients.

trans-DICHLOROETHYLENE

Bio-Accumulative Potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Bio-Accumulative Potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Partition coefficient Pow: 2.7

HFC-134a Tetrafluoroethane

Partition coefficient Pow: 1.06

ETHANOL

Bio-Accumulative Potential Bioaccumulation is unlikely.

Partition coefficient No information available.

Mobility in soil

Mobility The product contains volatile substances which may spread in the atmosphere.

Ecological information on ingredients.

trans-DICHLOROETHYLENE

Mobility The product has poor water-solubility.

ETHANOL

Mobility The product is soluble in water.

Other adverse effects

Other adverse effects The product contains a substance or substances that will contribute to global warming (greenhouse effect).

13. Disposal considerations

Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

General Requirements for marking and labeling of package varies depending on mode of transport. If uncertain of proper markings and labeling, call MicroCare for assistance.

UN Number

SPR - HEAVY DUTY FLUX REMOVER - SUPRCLEAN, AEROSOL

UN No. (IMDG) UN1950

UN No. (ICAO) UN1950

UN proper shipping name

Proper shipping name (TDG) LIMITED QUANTITY

Proper shipping name (IMDG) UN1950 AEROSOLS, NON-FLAMMABLE, 2.2, LIMITED QUANTITY

Proper shipping name (ICAO) UN1950 AEROSOLS, NON-FLAMMABLE, 2.2, LIMITED QUANTITY

Proper shipping name (DOT) LIMITED QUANTITY

Transport hazard class(es)

IMDG Class 2.2 LIMITED QUANTITY

ICAO class/division 2.2 LIMITED QUANTITY

ICAO subsidiary risk N/A

Packing group

TDG Packing Group N/A

IMDG packing group N/A

ICAO packing group N/A

DOT packing group N/A

Special precautions for user

Not applicable.

EmS F-C, S-V

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable. No information required.

15. Regulatory information**US Federal Regulations****SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities**

Not listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)*trans-DICHLOROETHYLENE*

Final CERCLA RQ: 1000(454) pounds (Kilograms)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

Not listed.

SARA 313 Emission Reporting

Not listed.

CAA Accidental Release Prevention

Not listed.

SARA (311/312) Hazard Categories

Pressure

SPR - HEAVY DUTY FLUX REMOVER - SUPRCLEAN, AEROSOL

OSHA Highly Hazardous Chemicals

Not listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

Not listed.

California Air Toxics "Hot Spots" (A-I)

Not listed.

California Air Toxics "Hot Spots" (A-II)

Not listed.

California Directors List of Hazardous Substances

trans-DICHLOROETHYLENE

Present.

ETHANOL

Present.

Massachusetts "Right To Know" List

trans-DICHLOROETHYLENE

Present.

ETHANOL

Present.

Rhode Island "Right To Know" List

ETHANOL

Present.

Minnesota "Right To Know" List

ETHANOL

Present.

HFC-134a Tetrafluoroethane

Present.

New Jersey "Right To Know" List

ETHANOL

Present.

Pennsylvania "Right To Know" List

trans-DICHLOROETHYLENE

Present.

ETHANOL

Present.

Inventories

Canada - DSL/NDSL

Yes

trans-DICHLOROETHYLENE

DSL

SPR - HEAVY DUTY FLUX REMOVER - SUPRCLEAN, AEROSOL

1,1,1,2,2,3,4,5,5,5-decafluoropentane

DSL

ETHANOL

DSL

HFC-134a Tetrafluoroethane

DSL

US - TSCA

Yes

trans-DICHLOROETHYLENE

Present.

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Present.

1,1,1,2,2,3,4,5,5,5-DECAFLUOROPENTANE (CAS# 138495-42-8) is controlled by TSCA Section 5, Significant New Use Rule

(SNUR; 40 CFR 721.5645) The approved uses are: precision and general cleaning, carrier fluid, displacement drying, printed circuit board cleaning, particulate removal and film cleaning, process medium, heat transfer fluid (dielectric and non-dielectric), and test fluid. Processors and users of this substance must also comply with the applicable general SNUR requirements set forth in 40 CFR 721 subpart A, including export notification requirements if applicable (40 CFR 721.20), and the applicable record keeping requirements set forth at 40 CFR 721.125.

1,1,1,2,2,3,4,5,5,5-Decafluoropentane 138495-42-8

The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product. This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D:

ETHANOL

Present.

HFC-134a Tetrafluoroethane

Present.

16. Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	2/23/2018
Revision	66
Supersedes date	12/13/2017
SDS No.	AEROSOL - SPR
SDS status	Approved.
Hazard statements in full	H225 Highly flammable liquid and vapor. H280 Contains gas under pressure; may explode if heated. H332 Harmful if inhaled.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.